SYNTHETIC DYE - OCHRE Réf.: 302540

Caracteristics

In 500ml jar

Allows you to add color to cement floors, slabs, screeds, tiles, terrazzo, terrazzo, mosaics, coatings, plaster, interlocking paving stones, etc.

- The color remains stable whatever the material used
- Wide variety of colors with strong coloring power

USF

- The coloring must be mixed with dry cement. Add the sand then the water last.
- The dosage is carried out by weight in relation to the cement. The percentage ranges from 1 to 6% depending on the desired shade.
- The rendering varies depending on the quantities of pigment but also the aggregates used. It is very important to carry out a test on a small area to validate the desired color before starting work. The density of the dye varies depending on the color.
- Take into account the weight and not the volume.



Product data

G	Artikelnr.		EAN Code	g g
	302540	6	3479133025407	500



NOVALIA SAS 2 rue de Bergognon 42500 LE CHAMBON F. FRANCE - www.novalia.pro

PEDDINGHAUS Handwerkzeuge In der Graslake 35 58332 Schwelm DEUTSCHLAND - www.peddinghaus.de **NOVALIA SA** Str. Narciselor nr.50 500251 - Braşov ROMÂNIA www.mob-ius.ro

NOVALIA ESPAÑA Portuetxe 51, of.204 20018 San Sebastián