LEVPANO® I Réf.: 513000

Caracteristics

3 POSSIBLE POSITIONS: horizontal installation up to 4.50m (with extension, 3.50m without extension), installation under eaves up to 3.50m (mast height) and vertical installation up to 5.90m (maximum height with a 3m plate. Mast height 4.50m with extension, 3.50m without extension). SAFETY GUARANTEED: Safety system consisting of 2 cables: 1 working cable and 1 anti-fall safety cable - PATENTED. 2 ANTI-DUMPING PLATFORMS on which the plate can be mounted. Withstands 150 kg. Validated by Socotec. Quick assembly of the boards using a captive screw system. Rounded edges and corners. Quality anti-slip coating. QUICK INSTALLATION: Ultra-fast Clip&Go system: quick locking and unlocking of arms and legs in a single movement - PATENTED. Saves time on site. PROTECTED AND RESTRAINED PLATE: 8 non-slip pads provide excellent support for the plate. The panel is held in place whatever its size thanks to 2 folding central arms and 2 telescopic end arms. USE THE ROTATION PLATE TO SWITCH FROM CRAWLING TO VERTI-CAL MODE. The head rotates using a simple pin, so there's no need to dismantle it. Saves time and effort. FOLD-OUT SABOTS: These hold the plate and fold away when the ceiling is reached to wedge the plate against the previous one without any gap. - PATENTED. OFFSET HANDLE: The guide handle is not located under the panel. The user's position is offset for better visibility and control. This also means that the operator's head is not under the Levpano when lowering the load. Horizontal loading height: 0.82 m for a horizontal installation of 3.50 m. 1m extension integrated into the column for horizontal installation up to 4.50m. Indexing every 10 cm to limit loading height - PATENTED. Simple, effective head tilting handle - PATENTED. 4 Ø 125 mm wheels fitted with a pivot and rolling lock system MONDELIN QUALITY: Complies with European Directive 2006/42/EC. Compliance examination carried out by SOCO-TEC. Each Levpano is individually assembled and tested. Delivered pre-assembled. Made in France, in our factory. Watch our videos showing how to use, assemble or change the cable: https://mondelin.fr/incontournables/ leve-plaque-levpano-mondelin



Product data

Installation hight m	Loading height m	Platform height m	Max. load kg	∠ kg	G			
4,5	0,82	0,49	75 et 60 avec rallonge	52	5	513000	1	3479135130000



NOVALIA SAS 2 rue de Bergognon 42500 LE CHAMBON F. FRANCE - www.novalia.pro

PEDDINGHAUS Handwerkzeuge In der Graslake 35 58332 Schwelm DEUTSCHLAND - www.peddinghaus.de NOVALIA SA Str. Narciselor nr.50 500251 - Braşov ROMÂNIA www.mob-ius.ro

NOVALIA ESPAÑA Portuetxe 51, of.204 20018 San Sebastián