

LEVPANO COMBI® Réf.: 517000

Characteristics

For simple and safe intensive vertical installation
3 installation options: horizontal, under slopes and vertical

LOW LOADING HEIGHT
- 68 cm for the 4m model
- 81cm for the 4.50m model

ERGONOMIC HANDLEBARS - PATENTED
The handlebar makes handling the plates ultra-simple, and is equipped with 2 levers:
- 1 for 90° pivoting of the beam and arms
- 1 for tilting the head

SAFETY SYSTEM consisting of 2 cables - PATENTED
- 1 working cable
- 1 anti-fall safety cable

FOLDING and adjustable PADS for fitting plasterboard of all widths 0.60m, 0.90m and 1.20m - PATENTED

FLOOR SPACE
- Horizontal installation and under slopes: 1.02 x 1.02 x 1.02 m
- Vertical installation: 1.09 x 0.94 x 0.94 m

EASY TO HANDLE
- Ergonomic handlebars for effortless handling of the panels
- Braking system integrated into the non-return winch, attached to the guide handle. This makes the machine extremely manoeuvrable
- 3 Ø 160 mm wheels for easy movement over rough surfaces, particularly with heavier fireproof panels or gypsum and cellulose boards, fitted with a locking system
- 2 transport wheels for moving when closed
- Low loading height

GUARANTEED SAFETY
8 anti-slip pads to keep the plate firmly in place
- Offset handle: the guide handle is not located under the plate. The user is off-set to give better visibility and more control. This also means you don't have to put your head under the Levpano when descending.

PRACTICAL
- Quick to assemble and dismantle
- A real platform on which you can climb to fix the plate.

FEATURES
- Aluminium column for a payload of 80 kg
- Platform: 0.50 x 0.62 m, thickness: 25 mm, height: 0.49 m and strength: 150 kg
- Plasterboard of all widths: 0.60 m, 0.90 m and 1.20 m, thanks to the retractable and adjustable shoes on the Levpano arm (patented) and thanks to the adjustable arms opposite the shoes
- Maximum opening of end arms: 3.10 m
- Minimum height of horizontal plate: 1.19 m = work surface.

OUR GUARANTEES :
- Complies with CE standards and European Directive 2006/42/EC
- Compliance examination carried out by SOCOTEC
- Each Levpano is individually assembled and tested
- Delivered pre-assembled

WORKPLATFORM supplied with the appliance, adaptable to horizontal or under-roof configurations





NOVALIA SAS 2 rue de Bergognon 42500 LE CHAMBON F.
FRANCE - www.novalia.pro
PEDDINGHAUS Handwerkzeuge In der Graslake 35
58332 Schwelm DEUTSCHLAND - www.peddinghaus.de
NOVALIA SA Str. Narciselor nr.50 500251 - Braşov ROMÂNIA
www.mob-ius.ro
NOVALIA ESPAÑA Portuete 51, of.204 20018 San Sebastián

LEVPANO COMBI® Réf.: 517000



Product data

Hauteur de pose horizontale m / Horizontal installation height m	Hauteur de pose verticale m / Vertical installation height m	Hauteur de chargement m / Loading height m	Hauteur plateforme m / Platform height m	Charge utile kg / payload kg	 kg	Garantie (nb d'année) / G	Ref.		Code EAN
4	5,40	0,68	0,49	80	53	5	516500	1	3479135165002
4,50	5,90	0,81	0,49	80	55	5	517000	1	3479135170006



NOVALIA SAS 2 rue de Bergognon 42500 LE CHAMBON F. FRANCE - www.novalia.pro
PEDDINGHAUS Handwerkzeuge In der Graslake 35 58332 Schwelm DEUTSCHLAND - www.peddinghaus.de
NOVALIA SA Str. Narciselor nr.50 500251 - Braşov ROMÂNIA www.mob-ius.ro
NOVALIA ESPAÑA Portuete 51, of.204 20018 San Sebastián